QUICK INSTRUCTION GUIDE

D39ASSL-SB | SHAPE & STRAIGHT SNIPS

Quick operating instructions • Keep this sheet for reference

PURPOSE

For continuous straight and curved cuts in sheet metal. Compact cutter head improves access and precision.

MODEL D39ASSL-SB

Left-cutting compound-leverage snips with central latch and reduced handle opening.

BEFORE YOU START

- Inspect blades, screwed pivot, spring and handles for wear or damage.
- Wear safety glasses and cut-resistant gloves; securely support the sheet.
- Mark the cut and verify that material thickness is within rated capacity.

HOW TO USE

1. Secure the workpiece and mark the intended straight or curved cutting path.
2. Release the centrally positioned latch and open the handles carefully.
3. Position the compact cutter head at the starting edge of the marked line.
4. Align the left-cutting blades with the cut; keep fingers clear of the joint.
5. Squeeze the handles steadily; use the compound leverage for controlled cuts.
6. Advance through straight sections with overlapping strokes for a clean edge.
7. For curves, turn gradually in the left-cutting direction without twisting blades.
8. Keep offcuts clear; never force material beyond the rated cutting thickness.
9. Inspect and deburr sharp edges; clean the snips and close the latch after use.

IMPORTANT SAFETY NOTES

- Cut edges and offcuts are sharp; wear eye and hand protection.
- Keep fingers away from cutting blades and moving joint components.
- Do not twist the snips or exceed their rated material capacity.

CARE AND STORAGE

Remove debris, inspect blades and pivot, and store clean, dry and latched.

SPECIFICATIONS

Cutting direction: Left; compact head; central handle latch.

Overall length: 230 mm (9"); blade length: 30 mm (1-3/16").

Rated sheet thickness: 1.2 mm at 600 N/mm²; weight: 0.50 kg.

HELP AND REFERENCE

Manufacturer instructions: Refer to BESSEY D39ASSL-SB product guidance.

Customer support: rapidmaterials.com

IMPORTANT: This quick guide does not replace manufacturer instructions.