



TRESPA® METEON® FR, Metallics (M, LM) TRESPA® METEON®

Final Assembly: Weert, the Netherlands

Life Expectancy: 50 Year(s)

Embodied Carbon: 14.5 kg CO2 eq

Declared Unit: m2

End of Life Options: Landfill (100%)

Ingredients:

Pulp, cellulose; Phenol, polymer with formaldehyde; Hexane, 1,6-diisocyanato-, homopolymer, 2-hydroxyethyl acrylate-blocked; C.I. Acid Black 2; Phenol; Ethanol, 2-(2-butoxyethoxy)-; Diethylene Glycol; Butanamide, N-(2,3-dihydro-2-oxo-1H-benzimidazol-5-yl)-3-oxo-2-[[2-(trifluoromethyl)phenyl]azo]-; C.I. Pigment Brown 24; C.I. Pigment Yellow 53; Diiron Trioxide; Tin oxide (SnO2); Carbon black; iron manganese trioxide; Pyrrolo[3,4-c]pyrrole-1,4-dione, 3,6-bis(4-chlorophenyl)-2,5-dihydro-; Quino[2,3-b]acridine-7,14-dione, 5,12-dihydro-; Titanium dioxide

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

% Disclosed: 100% at 100ppm

☒ LBC Red List Approved

VOC Content: Not Applicable

☐ Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Product Available with FSC Chain of Custody

TSP-0007

EXP. 01 AUG 2025

Original Issue Date: 2024

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare