



0411 | AKKU LOK'N'BAK

Quick operating instructions • Keep this sheet for reference

PURPOSE

Closes compatible single-lock and double-lock standing seams using a cordless drill and flexible drive shaft.

MODEL 0411

Cordless-drill-driven seamer for straight or curved roofing panels.

BEFORE YOU START

- Check seam profile, material thickness and properly secured roof panels.
- Verify seam height, curvature, machine condition and cordless drill compatibility.
- Use appropriate fall protection; secure the machine against falling.

HOW TO USE

1. Confirm profile, material thickness and panel configuration are compatible.
2. Set guide wheels for 1 in, 1-1/4 in or 1-1/2 in standing seam height.
3. Adjust seaming pressure for the material per manufacturer instructions.
4. For curved panels, adjust the machine radius within its rated range.
5. Select single-lock or double-lock operation with the designated lever.
6. Secure the included flexible shaft to the machine and a compatible cordless drill.
7. Position and engage the machine at the beginning of the standing seam.
8. Run the drill forward; walk alongside, controlling the drill and flexible shaft.
9. Monitor travel; keep the path clear and the shaft away from moving components.
10. At seam end, stop the drill; open the front lever and select reverse to return.
11. Stop, disengage safely and inspect the finished seam for consistent closure.

IMPORTANT SAFETY NOTES

- Keep hands, clothing and the flexible shaft clear of moving parts.
- Operate only within rated profile, thickness, seam height and curvature limits.
- Trained operators only; follow the full WUKO manual and roofing requirements.

CARE AND STORAGE

Disconnect the drill, inspect and clean machine and shaft, and store securely.

HELP AND REFERENCE

Follow the official WUKO 0411 manual. Customer support: rapidmaterials.com

IMPORTANT: A compatible cordless drill is required and is not included.