QUICK INSTRUCTION GUIDE

1002B | SEAM HAMMER

Quick operating instructions • Keep this sheet for reference

PURPOSE	MODEL 1002B
Powered hammering tool for progressively closing compatible, pre-fabricated standing seams.	Designed for prepared seams up to 30 mm (1-3/16 in) high.

BEFORE YOU START

- Check seam profile, height and material thickness against rated capacity.
- Secure the metal workpiece and inspect the forming head and power cord.
- Use suitable eye, hand and hearing protection; verify the electrical supply.

HOW TO USE

1. Confirm that the prepared standing seam height and metal thickness are within rated limits.
2. Secure and support the sheet metal to prevent movement while closing the seam.
3. Inspect the hammer and cord; connect to the electrical supply specified for the tool.
4. Align the forming head with the prepared seam at its starting point, as instructed.
5. Activate the tool and guide it along the seam; let the powered hammer close the fold.
6. Keep the tool aligned and move at a steady, controlled working pace.
7. Continue until the required section is closed; stop the tool before removing it.
8. Inspect the completed seam for uniform closure, damage or irregularities.
9. Disconnect power before adjustments, cleaning or storage.

IMPORTANT SAFETY NOTES

- Keep hands clear of the forming head and moving parts.
- Wear eye, hand and hearing protection; secure the workpiece.
- Disconnect power before service; do not exceed tool capacity.

CARE AND STORAGE

Disconnect power; remove debris and inspect the forming head before storage.

SPECIFICATIONS

Maximum prepared seam height: 30 mm (1-3/16 in).

Power and material limits: Consult the specific WUKO operating manual.

HELP AND REFERENCE

Manufacturer instructions: Consult the official WUKO 1002B manual.

Customer support: rapidmaterials.com

IMPORTANT: This quick guide does not replace complete manufacturer instructions.