QUICK INSTRUCTION GUIDE

1004852 | FLAT NOSE PLIERS

Quick operating instructions • Keep this sheet for reference

PURPOSE	MODEL 1004852
Narrow flat jaws grip and form localized bends, corners and detailed sheet metal flashings.	Manual flat-nose pliers with serrated gripping jaws.

BEFORE YOU START

- Support the sheet metal on a stable work surface.
- Wear suitable gloves and eye protection; watch for sharp edges.
- Protect sensitive finishes from marks made by serrated jaws.

HOW TO USE

1. Place the sheet metal on a stable work surface and identify the area to bend, grip, straighten or adjust.
2. Measure and mark the bend line or forming location when accuracy is needed.
3. Open the pliers and position the narrow flat jaws over the edge or detail.
4. Insert the material to the desired depth; align the jaws with the marked location.
5. Apply steady, controlled pressure to grip the metal securely between the serrated jaws.
6. Carefully rotate or reposition the pliers to bend, form a corner or adjust the edge.
7. For longer bends, work along the piece with small, overlapping adjustments.
8. Form corners and intricate flashing details gradually to minimize surrounding distortion.
9. Inspect alignment, consistency of forming and unwanted surface marks.

IMPORTANT SAFETY NOTES

- Serrated jaws can mark painted, polished or sensitive finishes.
- Keep fingers clear of jaws; never apply excessive force.
- Material capacity varies by alloy, temper and operation.

CARE AND STORAGE

Remove debris; inspect and clean jaws; store dry and protected.

SPECIFICATIONS

Tool: manual flat-nose sheet metal forming and gripping pliers.

Maximum material thickness: not verified for this model.

HELP AND REFERENCE

Manufacturer instructions: Consult the official WUKO 1004852 guidance.

Customer support: rapidmaterials.com

IMPORTANT: This quick guide does not replace manufacturer instructions.